

Product Specification

Base Oil	Synthetic
Colour	Light Yellow
Texture	Tacky
ASTM Penetration	min 170 in Bulk form min 80 in Stick form
Drop Point	None
Compatibility	Excellent
Solvent Resistance	Excellent
Special Additives	Lubricity Agent
Composition	Semi liquid to Stick Grade
Temperature Range	-24 °C to +180°C

Order Details

Ordering Size

Part No.

A Stick – 6.35 × 22.23 (mm) – 90/ Box	HRF-1000-90 A
B Stick – 10.32 × 34.93 (mm) – 48/ Box	HRF-1000-48 B
C Stick – 13.89 × 50.80 (mm) – 24/ Box	HRF-1000-24 C
D Stick – 16.67 × 73.02 (mm) – 24/ Box	HRF-1000-24 D
G Stick – 21.83 × 85.73 (mm) – 24/ Box	HRF-1000-24 G
J Stick – 37.31 × 222.25 (mm) – 4/Box	HRF-1000-4 J
J Stick – 37.31 × 222.25 (mm) – 6/Box	HRF-1000-6 J
J Stick – 37.31 × 222.25 (mm) – 12 /Box	HRF-1000-12 J
K Stick – 38.89 × 254.00 (mm) – 4/Box	HRF-1000-4 K
K Stick – 38.89 × 254.00 (mm) – 6/Box	HRF-1000-6 K
K Stick – 38.89 × 254.00 (mm) – 12 /Box	HRF-1000-12 K
4.5 Kg Tin	HRF-1000-4.5 Kg
18 Kg Pail	HRF-1000-18 Kg
250 gr. Tube	HRF-1000-0.3 T

RAGA HRF-1000 ماده روانکاری و آببندی شیرآلات Ball ، Plug و Gate از نوع سنتتیک می باشد.

RAGA HRF-1000 جهت استفاده در خطوط انتقال حلال های هیدروکربنی مانند بنزین، تولوئن و هر جا که نیاز به مقاومت بالا در برابر هیدروکربن ها باشد به کار برده می شود. RAGA HRF-1000 برای استفاده در شیرآلات خطوط لوله پخش فرآورده های نفتی مناسب بوده و طول عمر بالایی دارد.

RAGA HRF-1000 Valve Sealant and Lubricant is formulated from non-toxic and high viscosity synthetic base oil to assure excellent lubrication and sealing in a wide range of general purpose application where resistance to aliphatic hydrocarbons is required. RAGA HRF-1000 is recommended for Plug, Ball and Gate valves to use in refinery and petrochemical transfer pipelines.

