

- Metabo S-automatic torque limiting clutch: to limit any sudden reverse torque that can occur if tools jam or get caught •
- Easy saw blade replacement with spindle lock •
- Sturdy aluminum die cast saw housing •
- Fully closed guide plate for secure support •
- Clearly visible cutting indicator for sawing after initial cut •
- Cutting indicator can be set precisely •
- Safety lock switch to prevent unintentional start of the machine •
- Angle adjustment of the sawing blade to the guide plate can be aligned for maximum cutting precision •
- point guide for angle-precise bevel cuts up to 45°-4 •
- Lubrication system for long service life of the gear •
- .Optimum sawing dust ejection. No loading of machine with sawdust •
- External extraction possible: a vacuum cleaner can be connected •
- Extraction nozzle rotatable and stoppable •
- Auto-stop carbon brushes to protect the motor •
- (Precision guide rail available as accessory (order no. 6.31250) •

:Comparative technical values

Nm 9	Torque
mm 66	Maximum cutting depth at 90°
mm 47	Maximum cutting depth at 45°
mm 66 - 0	Cutting depth adjustable
mm 190	Saw blade diameter
min/ 4.200	No load speed
W 1.400	Rated input power
W 800	Output power
min/ 3.200	Rated load speed
m/s 28	Cutting speed at rated load
kg 5,5	(Weight (without mains cable

Scope of delivery

- (carbide thin circular saw blade (14 teeth •
- parallel guide/ripping fence •
- hexagon spanner •